ATOSA USA, INC.
Toll Free: 855-855-0399 Email: info@atosausa.com
www.atosa.com | www.atosausa.com
California, Colorado, Florida, Georgia, Illinois,
New Jersey, Ohio, Texas, Washington

"WE MAKE THE KITCHEN BETTER!"

MODELS:

CRDC-35 / CRDC-46 / CRDS-42 / CRDS-56

Countertop Refrigerated Display Cases - Curved/Square

Standard Features

- Stainless steel exterior & interior with black frames
- Rear mount compressor with environmentally friendly R290 refrigerant
- Electronic Temperature Controller
- Two (2) stainless steel shelves standard
- Defog feature to ensure the glass stays clear
- Maintains temperatures between 35°F – 38°F
- Magnetic door gasket(s) standard for positive door seal
- Two (2) rear sliding doors
- LED interior lighting
- Leveling legs
- NEMA 5-15 plug

CRDC-35



CRDC-46



CRDS-56

CRDS-42

For the best results of food preservation we recommend setting your refrigerator between 35 °F to 38 °F

1. Don't forget to leave the unit some room to breathe!
2. Please clean the condenser frequently to give the unit more fresh air.

3 YEAR PARTS AND LABOR WARRANTY
5 YEAR COMPRESSOR PART WARRANTY

REV. 07/26

ATOSA USA, INC.
Toll Free: 855-855-0399 Email: info@atosausa.com
www.atosa.com | www.atosausa.com
California, Colorado, Florida, Georgia, Illinois,
New Jersey, Ohio, Texas, Washington

"WE MAKE THE KITCHEN BETTER!"

SPECIFICATIONS

Models	Door	Capacity (Cu.Ft.)	Shelves	Rated Current (A)	Voltage (V/Hz/Ph)	HP	Refrigerant	Exterior Dimensions (inch)	Net Weight (lb)	Gross Weight (lb)
CRDC-35	2	3.5	2	2	115/60/1	1/5	R290	$27^{5/8}\times22^{1/8}\times26^{7/8}$	139	172
CRDC-46	2	4.6	2	2	115/60/1	1/5	R290	$35^{1/2}\times22^{1/8}\times26^{7/8}$	154	200
CRDS-42	2	4.2	2	2	115/60/1	1/5	R290	$27^{5/8}\times22^{1/8}\times26^{5/8}$	143	192
CRDS-56	2	5.6	2	2	115/60/1	1/5	R290	$35^{1/2}\times22^{1/8}\times26^{5/8}$	165	214

PLAN VIEW

CRDC-35



CRDC-46





Side View

CRDS-42



CRDS-56





Side View

LED lights